查询BT136S series E供应商

Triacs sensitive gate

BT136S series E

GENERAL DESCRIPTION

Passivated, sensitive gate triacs in a plastic envelope, suitable for surface mounting, intended for use in general purpose bidirectional switching and phase control applications, where high sensitivity is required in all four quadrants.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	MAX.	UNIT
	BT136S-	**600E**	**800E**	
V_{DRM}	Repetitive peak off-state voltages	600	800	V
$I_{T(RMS)}$	RMS on-state current	4	4	A
I_{TSM}	Non-repetitive peak on-state current	25	25	A

PINNING - SOT428

PIN	DESCRIPTION
1	MT1
2	MT2
3	gate
tab	MT2

PIN CONFIGURATION



SYMBOL



LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.		UNIT
				-600	**-800**	
V_{DRM}	Repetitive peak off-state voltages		-	600[1]	800	V
$I_{T(RMS)}$	RMS on-state current	full sine wave; $T_{mb} \leq 107$ ˚C	-	4		A
I_{TSM}	Non-repetitive peak on-state current	full sine wave; $T_j = 25$ ˚C prior to surge				
		t = 20 ms	-	25		A
		t = 16.7 ms	-	27		A
I^2t	I^2t for fusing	t = 10 ms	-	3.1		A^2s
dI_T/dt	Repetitive rate of rise of on-state current after triggering	I_{TM} = 6 A; I_G = 0.2 A; dI_G/dt = 0.2 A/µs				
		T2+ G+	-	50		A/µs
		T2+ G-	-	50		A/µs
		T2- G-	-	50		A/µs
		T2- G+	-	10		A/µs
I_{GM}	Peak gate current		-	2		A
V_{GM}	Peak gate voltage		-	5		V
P_{GM}	Peak gate power		-	5		W
$P_{G(AV)}$	Average gate power	over any 20 ms period	-	0.5		W
T_{stg}	Storage temperature		-40	150		˚C
T_j	Operating junction temperature		-	125		˚C

1 Although not recommended, off-state voltages up to 800V may be applied without damage, but the triac may switch to the on-state. The rate of rise of current should not exceed 3 A/µs.

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j\text{-}mb}$	Thermal resistance junction to mounting base	full cycle	-	-	3.0	K/W
		half cycle	-	-	3.7	K/W
$R_{th\ j\text{-}a}$	Thermal resistance junction to ambient	pcb (FR4) mounted; footprint as in Fig.14	-	75	-	K/W

STATIC CHARACTERISTICS

T_j = 25 ˚C unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS		MIN.	TYP.	MAX.	UNIT
I_{GT}	Gate trigger current	V_D = 12 V; I_T = 0.1 A					
			T2+ G+	-	2.5	10	mA
			T2+ G-	-	4.0	10	mA
			T2- G-	-	5.0	10	mA
			T2- G+	-	11	25	mA
I_L	Latching current	V_D = 12 V; I_{GT} = 0.1 A					
			T2+ G+	-	3.0	15	mA
			T2+ G-	-	10	20	mA
			T2- G-	-	2.5	15	mA
			T2- G+	-	4.0	20	mA
I_H	Holding current	V_D = 12 V; I_{GT} = 0.1 A		-	2.2	15	mA
V_T	On-state voltage	I_T = 5 A		-	1.4	1.70	V
V_{GT}	Gate trigger voltage	V_D = 12 V; I_T = 0.1 A		-	0.7	1.5	V
		V_D = 400 V; I_T = 0.1 A; T_j = 125 ˚C		0.25	0.4	-	V
I_D	Off-state leakage current	V_D = $V_{DRM(max)}$; T_j = 125 ˚C		-	0.1	0.5	mA

DYNAMIC CHARACTERISTICS

T_j = 25 ˚C unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
dV_D/dt	Critical rate of rise of off-state voltage	V_{DM} = 67% $V_{DRM(max)}$; T_j = 125 ˚C; exponential waveform; gate open circuit	-	50	-	V/µs
t_{gt}	Gate controlled turn-on time	I_{TM} = 6 A; V_D = $V_{DRM(max)}$; I_G = 0.1 A; dI_G/dt = 5 A/µs	-	2	-	µs



Fig.1. Maximum on-state dissipation, P_{tot}, versus rms on-state current, $I_{T(RMS)}$, where α = conduction angle.



Fig.4. Maximum permissible rms current $I_{T(RMS)}$, versus mounting base temperature T_{mb}.



Fig.2. Maximum permissible non-repetitive peak on-state current I_{TSM}, versus pulse width t_p, for sinusoidal currents, $t_p \leq 20ms$.



Fig.5. Maximum permissible repetitive rms on-state current $I_{T(RMS)}$, versus surge duration, for sinusoidal currents, f = 50 Hz; $T_{mb} \leq 107^{\circ}C$.



Fig.3. Maximum permissible non-repetitive peak on-state current I_{TSM}, versus number of cycles, for sinusoidal currents, f = 50 Hz.



Fig.6. Normalised gate trigger voltage $V_{GT}(T_j)/ V_{GT}(25^{\circ}C)$, versus junction temperature T_j.



Fig.7. Normalised gate trigger current $I_{GT}(T_j)/ I_{GT}(25˚C)$, versus junction temperature T_j.



Fig.8. Normalised latching current $I_L(T_j)/ I_L(25˚C)$, versus junction temperature T_j.



Fig.9. Normalised holding current $I_H(T_j)/ I_H(25˚C)$, versus junction temperature T_j.



Fig.10. Typical and maximum on-state characteristic.



Fig.11. Transient thermal impedance $Z_{th\ j\text{-}mb}$, versus pulse width t_p.



Fig.12. Typical, critical rate of rise of off-state voltage, dV_D/dt versus junction temperature T_j.

MECHANICAL DATA

Dimensions in mm

Net Mass: 1.1 g



Fig.13. SOT428 : centre pin connected to tab.

MOUNTING INSTRUCTIONS

Dimensions in mm



Fig.14. SOT428 : minimum pad sizes for surface mounting.

Notes
1. Plastic meets UL94 V0 at 1/8".

DEFINITIONS

DATA SHEET STATUS		
DATA SHEET STATUS[2]	**PRODUCT STATUS**[3]	**DEFINITIONS**
Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice
Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in ordere to improve the design and supply the best possible product
Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Changes will be communicated according to the Customer Product/Process Change Notification (CPCN) procedure SNW-SQ-650A
Limiting values		
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.		
Application information		
Where application information is given, it is advisory and does not form part of the specification.		
© **Philips Electronics N.V. 2001**		
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.		
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.		

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

2 Please consult the most recently issued datasheet before initiating or completing a design.

3 The product status of the device(s) described in this datasheet may have changed since this datasheet was published. The latest information is available on the Internet at URL http://www.semiconductors.philips.com.